



SAFETY DATA SHEET

SECTION 1 – PRODUCT AND COMPANY INFORMATION

Product Name: S Lube 46

Product Code: 3003100820

Product Type: Synthetic Lubricant Compressor Fluid

Intended Use: Industrial compressor Lubricant

Supplier:

Edmac

11313 Steele Creek Road

Charlotte, NC 28273

Emergency Spill Information:

704-504-4066 (US)

SECTION 2 – COMPOSITION – INFORMATION ON INGREDIENTS

Reportable Hazardous Substance or Complex Substance

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SECTION 3 – HAZARDS IDENTIFICATION

GHS Product Classification: None

Emergency Overview: This product has been evaluated and does not require any hazard warning on the label under OSHA criteria. The product does not require a hazard warning label in accordance with GHS criteria according to REGULATION (EC) No 1272/2008.

Risk Phrases: None

Safety Phrases: S24, S26, S29/35, S36/37/39, S57, S62, S63

HMIS Code: (Health: 1) (Flammability: 1) (Physical Hazard: 0) (Protection: B)

NFPA Code: (Health: 1)

(Flammability: 1) (Reactivity: 0)

WHMIS Code: None

SECTION 4 – FIRST AID MEASURES

Eye: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Skin: After contact with skin, take off immediately all contaminated clothing, wash immediately with plenty of soap and water.

Inhalation: In case of accident by inhalation: remove casualty to fresh air and keep at rest.

Ingestion: If swallowed, do not induce vomiting: seek medical advice immediately.

Symptoms/effects: Mild irritation may occur with overexposure.

Special treatment: Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

Suitable Extinguishing Media: In case of fire use dry chemical, carbon dioxide, foam, steam, or water fog.

Unsuitable Extinguishing Media: Never use water.

Specific Hazards: Keep away from extreme heat and open flames.

Hazardous Combustion Products: Incomplete combustion results in oxides of carbon.

Fire Fighting Equipment: Fire fighters should wear an approved self-contained breathing apparatus.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions: Wear suitable protective clothing and gloves.

Environmental precautions: Use appropriate containment to avoid environmental contamination. Do not empty into drains; dispose of this material and its container in a safe way.

Methods and materials for cleanup: To clean the floor and all objects contaminated by this material use an inert absorbent material.

SECTION 7 – HANDLING AND STORAGE

Handling: No special requirements if handled with reasonable care. Keep containers closed when not in use. Wash thoroughly after handling. Empty container contains product residue which may exhibit hazards of product.

Storage: Keep in a cool place away from open flames. No special storage precautions required.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: In case of insufficient ventilation wear suitable respiratory equipment.

Protective Equipment: Wear suitable protective clothing, gloves and eye/face protection.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------|---|
| Appearance | : Clear, amber colored liquid |
| Odor | : Mild |
| Odor Threshold | : Not Determined |
| Apparent pH | : 7-8.5 Method: ASTM D1293 |
| Melting Point / Freezing Point | : Pour Point (-30 °F) |
| Initial Boiling Point | : Not applicable, decomposes |
| Flash Point | : 224°C (435 °F) (Base fluid) Method: ASTM D93 |
| Evaporation Rate | : Not determined |
| Flammability | : Not flammable |
| Upper/Lower Explosive Limits | : Not determined |
| Vapor Pressure | : < 0.133 kPa (1 mm Hg) at 20 ° ASTM D5482 |
| Vapor Density | : Not determined |
| Specific Gravity | : 0.85 g/cm ³ @ 25 °C Method: ASTM D1475 |
| Solubility in Water | : insoluble, floats on top of water. |
| Partition Coefficient | Not determined : Method: ASTM E1147 |
| Autoignition Temperature | Not determined Method: ASTM E659 |
| Decomposition Temperature | Not determined : Method: ASTM E2550 |
| Viscosity | 46. 2 cSt @ 40°C Method: ASTM D445 |

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability: Material is normally stable at moderately elevated temperatures and pressures.

Hazardous Reactions: None.

Conditions to Avoid: Keep away from extreme heat.

Materials to Avoid: Keep away from chlorine, fluorine, and other strong oxidizers.

Hazardous Decomposition Products: None identified.

SECTION 11 – TOXICOLOGICAL INFORMATION

Eye Contact: Mildly irritating to eyes.

Skin Contact: Prolonged or repeated contact may cause skin irritation. High pressure injection into or under the skin should be considered a medical emergency, and treated immediately.

Inhalation: Under normal conditions of intended use, this material is not expected to be an inhalation hazard. Base fluid data indicates LC 50 > 5000 mg/m³

Ingestion: No significant health hazards identified. Base fluid data indicated LD 50 > 5000 mg/kg.

Primary Routes of Entry: None identified.

- ACUTE EXPOSURE --

Toxicological testing has not been conducted on this product.

| | |
|---------------------------------|--|
| Dermal Toxicity | The LD 50 in rabbits is > 2000 mg/Kg. Based on data from components or similar materials. |
| Inhalation Toxicity | No data available to indicate product may be a toxic inhalation hazard, but not recommended for breathing air compressors. |
| Oral Toxicity | The LD50 in rats is > 5000 mg/kg. based on data from base fluid or similar materials. Swallowing material may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea, and abdominal pain. |
| Dermal Sensitization | No data available to indicate product may be a skin sensitizer. |
| Inhalation Sensitization | No data available to indicate product may be a respiratory sensitizer. |

-- CHRONIC EXPOSURE --

Toxicological testing has not been conducted on this formulated product. Available data from base fluid component does not indicate any specific concerns.

SECTION 12 – ECOLOGICAL INFORMATION

Environmental Effects: No known significant effects or critical hazards.

-- ENVIRONMENTAL TOXICITY --

Freshwater Fish Toxicity: Not determined.

-- ENVIRONMENTAL FATE --

Persistence and Degradability: Not determined

Bioaccumulative Potential: Not determined.

Mobility in Soil: Not determined.

Other Adverse Effects: None identified.

SECTION 13 – DISPOSAL INFORMATION

Do not empty into drains; dispose of this material and its container as non-hazardous waste.

US EPA Disposal as "Specification waste oil"

This material, if discarded, is not a hazardous waste under RCRA Regulation 40 CFR 261. This material, if discarded, should be considered a European non-hazardous waste in accordance with Directive 91/689/EC.

SECTION 14 – TRANSPORTATION INFORMATION

| | |
|---------------------------------|-----------------------|
| UN Number | Not regulated. |
| UN Proper Shipping Name: | Not regulated. |
| Transport Hazard Class | Not regulated. |
| Package Group | Not regulated. |
| Marine Pollutant | Not determined |
| Special Precautions | None |

SECTION 15 – REGULATORY INFORMATION

-- Global International Chemical Inventories --

| | |
|---------------|---|
| USA | All components of this material are on the US TSCA Inventory or are exempt. |
| EEC | All components are in compliance with the EC 7th Amendment Directive 92/32/EEC. |
| Canada | All components of this material are DSL listed or are exempt. |

-- Other U.S. Federal Regulations --

EPCRA: This material contains no extremely hazardous substances.

SARA 311 Classifications

| | |
|--|-----------|
| Fire Hazard | No |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |
| Immediate (Acute) Hazard | No |
| Delayed (Chronic) Hazard | No |

-- State Regulations --

California Proposition 65: Not known to contain any substances listed under Proposition 65, known to the State of California to cause cancer, birth defects or other reproductive harm, in concentrations which would require a warning under the statute.

SECTION 16 – OTHER INFORMATION

Label text:

Handling: No special requirements if handled with reasonable care.

First Aid:

Eye: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Skin: After contact with skin, take off immediately all contaminated clothing, wash immediately with plenty of soap and water.

Inhalation: In case of accident by inhalation: remove casualty to fresh air and keep at rest.

Ingestion: If swallowed, do not induce vomiting: seek medical advice immediately.

Fire: In case of fire use dry chemical, carbon dioxide, foam, steam, or water fog.

Spill or Leak: To clean the floor and all objects contaminated by this material use an inert absorbent material.

Date Revised: December 12, 3015

Supersedes: None

Date Prepared: 21 September 2015

The information provided herein is believed to be accurate to the best of the company's knowledge as of the date of its issue. We do not warrant or guarantee the information provided and will not be held liable for any loss or damage from its use.